



Affordable Holistic Home Security Solution

IQ Panel Integration

IQ Keypad seamlessly pairs with IQ4 NS, IQ Panel 4, IQ4 Hub and IQ Pro to provide tailored, customized security for every situation.



Range and Reliability

Reduce technician visits and enjoy hassle-free wireless with IQ Keypad. Quickly connect devices without frustrating mesh network configurations or unstable wireless communication and experience enhanced encryption and reliable data transmission.



Long Battery Life

IQ Keypad boasts an extended 3-year battery life, reducing the need for frequent site visits by dealers and ensuring the system is up and running for longer.





Responsive Control and Resilient Build

Sensitive touch technology on IQ Keypad provides highly responsive user control, while its durable construction protects it from everyday wear-and-tear such as dirt and dust.



Modern and Aesthetic in Two Colors

Choose between white or black color options to perfectly tailor your IQ Keypad to your home's aesthetic.



Budget-Friendly Security

IQ Keypad delivers an innovative arming solution in a cost-effective package without compromising on quality so users can enjoy exceptional security without breaking the bank.

Easy Installation

Simply mount the keypad to the wall, insert batteries, and follow a short automatic pairing process on IQ Panel and IQ Keypad will be ready to go.



Proximity Tag Reader (optional)

"IQ Keypad Proximity-PG" models support Proximity Tags, you may Arm with a Proximity Tag in place of a 4 - 6 digit code.



SPECIFICATIONS

Models	IQ Keypad-PG, IQ Keypad Prox-PG (includes Prox Tags)
Interface	Capacitive touch key mat (0-9, *, #, Arm Stay, Arm Away, Arm Night keys)
Wireless	PowerG 868 MHz
LED Indicator	Status LEDs (Trouble, Arming, Status)
Buzzer	1-for key presses, chirps, and alarms
Tamper Switch	Wall and Enclosure Tamper
Battery	4 x AA – Use only Energizer AA 1.5V Alkaline Battery
Dimensions	6.1"H x 4.6" W x .91" D (155mm x 117mm x 23mm)
Mount	Back plate, wall mount only
Certification	EN Grade 2, SBSC (Sweden), FFH (Finland), F&P (Denmark), FG (Norway), Incert (Belgium)
Operating Temperature	14 to 131F (-10 to 55C) Up to 93% relative humidity, indoor, dry ordinary locations use only (*)
Storage Temperature	-41.8 to 185F (-40 to 85C) Up to 95% relative humidity, indoor, dry ordinary locations only (*)